Swann™

Advanced security made easy™

professionalsecurity

Compact Day/Night Security Camera

PRO-555™

Clear CCD images
See more day & what's night with high quality video

Mount to walls or ceilings
Install easily where most needed

Visible deterrent
Deter intruders & protect property

See what you need to see
Compact size yet powerful

Quality aluminum materials
Robust housing & stand for all weather

- 420 high video quality 420 TV Lines CCD
- **50ft 15m** excellent night vision
- weather resistant robust metal casing
- BNC cable 60ft 18m
- easily connects to your TV & DVR

Product Code	SW331-PR5
UPC	814282011667
EAN	9325481011095

www.swannsecurity.com

Swann™

Advanced security made easy™

professionalsecurity

Compact Day/Night Security Camera

PRO-555™

Camera

Video

Image Sensor	1/4" CCD
Video Quality	420 TV Lines
Number of Effective Pixels	NTSC: 510 x 492 / PAL: 628 x 582
Minimum Illumination	0 Lux (IR on)
Day/Night Mode	Color during day / switches to B&W at night
White Balance	Automatic
Signal / Noise Ratio	> 50dB
Electronic Shutter	1/60 - 1/100,000 NTSC 1/50 - 1/100,000 PAL
Gain Control	Automatic
Backlight Compensation	Yes
Lens	6mm
Viewing Angle	41 degrees

Night Vision

Night Vision Distance	50ft / 15m
Number of Infra-Red LEDs	27
Infra-Red Wavelength	850nm
Infra-Red LED Life	10,000 hours

General

Operating Power	DC 12V
Operation Temperature	14°F to 122°F / -10°C to +50°C
Body Construction	Aluminum
Dimensions - Camera with stand	5.1" x 3.7" x 2.4" 130mm x 95mm x 60mm
Weight – Camera & Stand	15oz / 415g
Cable Length	60ft / 18m

Packaging

Pack Weight	9lbs / 4.2kg
Pack Dimensions (HxWxD)	10.6" x 8.3" x 4.1" / 270mm x 210mm x 103mm
Master Pack Quantity	6
Master Pack Dimensions (HxWxD)	20.1" x 11.8" x 12.6" / 510mm x 300mm x 320mm

Package Contents

all installation accessories included

- PRO-555™ Camera
- BNC cable 60ft / 18m
- BNC to RCA Adapter
- Power Adapter
- Mounting Screws & Plugs
- Operating Instructions
- Theft Deterrent Stickers x 4

Swann™

www.swannsecurity.com

Please note that the information contained within this document is subject to change without notification.
All trademarks remain properties of their respective owners